



INLET VALVE

DN	B [mm]	C [mm]	D [mm]	E [mm]	Ship Wt. [Kg]
6"	54	520	127	304	22
8"	63	520	152	276	27
10"	63	540	152	276	34
12"	76	603	203	400	68
16"	101	676	203	508	136
18"	108	717	203	508	152
20"	152	752	203	508	192

STANDARD FEATURES

- Heavy-duty design
- 60° cone
- Smooth interior
- Manway
- Butterfly valve with pneumatic actuator
- Rotatable outlet
- Erosion allowances on wear surface

OPTIONAL FEATURES

- Aeration jets
- Interior coatings
- Multiple inlets
- Stainless construction AISI 304/316
- Higher pressure and temperature ratings
- ATEX design 94/9/CE
- Electronic multi pressure control

SPECIFICATIONS

- Design pressure: 6 bar
- Temperature range: -10C° a +50C°
- PED 97/23/CE

27-01-2010

TRANSPORTER

Model No.	Capacity [Lt]	A [mm]	Dia.[mm]	Ship Wt. [Kg]
16-60-00.5	14	761	405	66
16-60-001	24	863	405	72
24-60-02.5	70	1066	609	122
24-60-005	140	1371	609	134
36-60-010	280	1600	914	400
36-60-015	490	1829	914	453
42-60-020	600	1905	1066	500
42-60-030	850	2285	1066	567
42-60-040	1100	2590	1066	635
54-60-060	1700	2743	1371	896
54-60-080	2200	3124	1371	1032
54-60-100	2800	3505	1371	1168
72-60-150	4200	3733	1829	1565
72-60-200	5600	4267	1829	1905
72-60-250	7000	4800	1829	2256
96-60-500	14000	5714	2438	3969
120-60-750	21200	6172	3048	4536
120-60-1000	28000	7162	3048	5216

DIMENSION SUBJECT TO CHANGE WITHOUT NOTICE

THE **NOL-TEC** TRANSPORTERS ARE DESIGNED TO PROVIDE TROUBLE-FREE DENSE PHASE PNEUMATIC CONVEYING OF MOST MATERIALS.